

## DESCRIPTION

CONTENT DISTRIBUTION SERVER AND CONTENT PLAYBACK  
CONTROL TERMINAL

5

## Technical Field

The present invention relates to a content distribution server that distributes content using a broadcast network or IP network channel and a content playback control terminal that controls playback of content distributed from a content distribution server.

## Background Art

15 There is a conventional digital content distribution system that uses DRM (Digital Rights Management) technology (refer to Patent Document 1). DRM technology enables usage restrictions relating to the number of playback times, transfer, duplication, and so forth to be set for distributed content.

Also, there is a conventional digital content distribution system that uses metadata stipulated by the TV-Anytime forum. According to the method stipulated by the TV-Anytime forum, the contents of a specific section of content (such as a CM, the first inning of a baseball game, or the first half

of a soccer match) are described by means of segmentation metadata.

In recent years, the increased capacities of HDDs installed in PVRs (Personal Video Recorders) and an automatic recording function have made it possible for a program to be recorded automatically and viewed by the user later. However, since special playback such as 30-second skipping, fast-forwarding, and jumping to a specified time can be freely used in recorded viewing, CMs are frequently skipped when a program is viewed, and the current CM business model in real-time broadcasting is becoming nonviable.

Also, even if it is wished to apply a broadcasting type of CM business model to content downloaded via an IP network, it is difficult to implement this since special playback can be freely performed with a playback player. However, in solving these problems, even though the number of times content is played back can be restricted by means of conventional DRM technology, there is no way of restricting the playback method, such as special playback. Furthermore, although it is possible to describe a specific section of a program as a CM section by means of segmentation metadata, there is no way of restricting special playback and so forth only for that section.

Patent Document 1: Unexamined Japanese Patent  
Publication No. 2002-342518

#### Disclosure of Invention

##### 5 Problems to be Solved by the Invention

However, the above conventional technology has  
a problem that there is no technique whereby  
playback control intended by a broadcaster performs  
restriction for individual specific sections of a  
10 program.

The present invention has been implemented  
taking into account the problems described above,  
and it is an object of the present invention to make  
it possible for the playback mode to be restricted  
15 for individual specific sections of content.

##### Means for Solving the Problems

In the present invention, a content  
distribution server distributes a content key,  
20 encrypted content encrypted using the content key,  
and playback control information that describes  
playback mode restrictions for a specific section  
of content to a content playback terminal, and the  
content playback terminal refers to the playback  
25 control information and decodes and plays back  
encrypted content in the case of a playback mode in  
which a specific section of content is not

restricted.

#### Advantages of the Invention

According to the present invention, playback  
5 of a specific section of content can be restricted  
based on playback control information.

#### Brief Description of Drawings

FIG. 1 is a block diagram showing the  
10 configuration of a content playback control system  
according to Embodiment 1 of the present invention;

FIG. 2 is a conceptual drawing showing the  
relationship between license information for  
encrypted content and playback control information  
15 in a content playback control system of Embodiment  
1;

FIG. 3 is a conceptual drawing showing  
relationships when issuer identification  
information is attached to license information for  
20 encrypted content and playback control information  
in a content playback control system of Embodiment  
1;

FIG. 4 is a conceptual drawing showing  
relationships when issuer identification  
25 information and an ID are attached to license  
information and playback control information for  
encrypted content in a content playback control

system of Embodiment 1;

FIG. 5 is a drawing showing an example of the schema of playback control information in a content playback control system of Embodiment 1;

5        FIG. 6 is a first drawing showing an example of metadata of playback control information in a content playback control system of Embodiment 1;

FIG. 7 is a second drawing showing an example of metadata of playback control information in a  
10 content playback control system of Embodiment 1;

FIG. 8 is a processing flowchart up to where a terminal obtains encrypted content, license information, and playback control information from a server in a content playback control system of  
15 Embodiment 1;

FIG. 9 is a processing flowchart up to where a terminal decodes encrypted content in accordance with license information in a content playback control system of Embodiment 1;

20        FIG. 10 is a processing flowchart showing a case where skip operation is performed in a CM section when playback based on the playback control information shown in FIG. 6 is performed in a content playback control system of Embodiment 1;

25        FIG. 11 is a block diagram showing the configuration of a content playback control system according to Embodiment 2 of the present invention;

FIG. 12 is a drawing showing an example of the schema of playback control information in a content playback control system of Embodiment 2;

FIG. 13 is a drawing showing an example of  
5 metadata of playback control information in a content playback control system of Embodiment 2;

FIG. 14 is a flowchart of content playback control in a content playback control system of Embodiment 2;

10 FIG. 15 is a block diagram showing the configuration of a content playback control system according to Embodiment 3 of the present invention;

FIG. 16 is a drawing showing an example of the schema of playback control information in a content  
15 playback control system of Embodiment 3;

FIG. 17 is a drawing showing an example of metadata of playback control information in a content playback control system of Embodiment 3;

FIG. 18 is a flowchart of content playback  
20 control in a content playback control system of Embodiment 3;

FIG. 19 is a block diagram showing the configuration of a content playback control system according to Embodiment 4 of the present invention;

25 FIG. 20 is a drawing showing an example of the schema of playback control information in a content playback control system of Embodiment 4;

FIG. 21 is a drawing showing an example of metadata of playback control information in a content playback control system of Embodiment 4;

FIG. 22 is a flowchart of content playback control in a content playback control system of Embodiment 4;

FIG. 23 is a drawing showing another example of the schema of playback control information in a content playback control system of Embodiment 4; and

FIG. 24 is a drawing showing another example of metadata of playback control information in a content playback control system of Embodiment 4.

#### Best Modes for Carrying Out the Invention

Content playback control systems according to embodiments of the present invention will now be described in detail with reference to the accompanying drawings.

#### (Embodiment 1)

FIG. 1 is a block diagram showing the configuration of a content playback control system according to Embodiment 1 of the present invention. In FIG. 1, a content playback control system has a configuration in which content distribution server (hereinafter referred to as "server") 100 serving as a transmitting apparatus of encrypted content,

license information, and playback control information, and content playback control terminal (hereinafter referred to as "terminal") 110, are connected via a broadcast network, IP network, or  
5 suchlike channel 120.

Server 100 generates encrypted content, license information, and playback control information, and transmits these to terminal 110 via a broadcast network, IP network, or suchlike channel  
10 120.

Server 100 has content encryption section 101, license information generation section 102, playback control information generation section 103, communication section 104, input section 105,  
15 content storage section 106, and content key storage section 107.

Server 100 according to Embodiment 1 is just one configuration example, and license information generation section 102, playback control  
20 information generation section 103, content storage section 106, and content key storage section 107 may be separate servers. Actually, possible patterns include a case where playback control information is produced by a content producer, a case where  
25 playback control information is produced by a content distributor, a case where there is a provider who produces only playback control



information, and so forth. Therefore, the server in which playback control information generation section 103 is located will vary according to these various cases.

5           Content control information stored in content storage section 106, that is, information that restricts the content playback mode, is input to playback control information generation section 103 from input section 105. Playback control  
10 information generation section 103 also has content stored in content storage section 106 as input, and analyzes content section information. Playback control information generation section 103 then establishes correspondence between the analyzed  
15 section information and control information input from input section 105, and generates playback control information for controlling the content playback method.

          Playback control information will be described  
20 in detail later.

          License information generation section 102 generates license information containing a content key for encrypting content, stored in content key storage section 107, and content key usage  
25 conditions for permitting only playback based on playback control information.

          Content encryption section 101 encrypts

content using the content key contained in the  
license information generated by license  
information generation section 102, and transmits  
this encrypted content to communication section  
5 104.

Communication section 104 is a section that  
performs data transmission/reception to/from  
terminal 110, and transmits encrypted content to  
terminal 110 via broadcast network, IP network, or  
10 suchlike channel 120.

The method of transmitting license information  
generated by the license information generation  
section to terminal 110 via communication section  
104 may be based on conditional access scheme,  
15 public key cryptography, or the like.

Terminal 110 receives encrypted content,  
license information, and playback control  
information from server 100 via broadcast network,  
IP network, or suchlike channel 120, and if playback  
20 based on the playback control information is  
permitted according to usage conditions of the  
license information, plays back content based on the  
playback control information.

Terminal 110 has communication section 111,  
25 content recording section 112, license information  
recording section 113, playback control information  
recording section 114, content decoding section 115,

license information processing section 116,  
playback control information processing section 117,  
and operating section 118.

Communication section 111 performs reception  
5 of data from server 100 via broadcast network or IP  
network channel 120.

Content recording section 112 is a recording  
medium for recording encrypted content received by  
communication section 111 or obtained from other  
10 recording mediums, and more specifically, is an HDD,  
DVD-RAM, an SD memory card, volatile memory,  
nonvolatile memory, an IC card, or the like. By this  
means, encrypted content can be obtained from server  
100 before being used, and encrypted content can  
15 also be obtained via other storage media.

License information recording section 113 is  
a recording medium for recording license  
information received by communication section 111  
or obtained from other recording medium, and more  
20 specifically, is an HDD, DVD-RAM, volatile memory,  
nonvolatile memory, an IC card, a memory card, or  
the like. By this means, license information can  
be obtained from server 100 before being used, and  
license information can also be obtained via other  
25 storage media.

Playback control information recording  
section 114 is a recording medium for recording

playback control information received by communication section 111 or obtained from other recording medium, and more specifically, is an HDD, DVD-RAM, an SD memory card, volatile memory, nonvolatile memory, an IC card, or the like. By this means, playback control information can be obtained from server 100 before being used, and playback control information can also be obtained via other storage media.

10        Using a content key passed from license information processing section 116, content decoding section 115 decodes encrypted content recorded in content recording section 112, and transmits this content to output terminal 130.

15        Output terminal 130 is a terminal that outputs content, and is composed of a monitor that displays images, a speaker that outputs sound, and so forth.

Content decoding section 115 must comply with license information usage conditions. Therefore, if "only playback based on playback control information is permitted" is specified in usage conditions, content decoding section 115 is not permitted to perform normal playback, and performs playback processing in accordance with the playback control information.

License information processing section 116 obtains license information containing a content

key and usage conditions from license information recording section 113, and only if the usage conditions are met, passes the content key to content decoding section 115 and permits decoding  
5 of encrypted content.

Here, as in the description of license information generation section 102, "only playback based on playback control information is permitted" is added to the usage conditions in addition to  
10 conditions that can be set with conventional DRM. License information is protected from unauthorized duplication or tampering by means of DRM technology.

Playback control information processing section 117 controls playback of content in content  
15 decoding section 115 based on playback control information. To be specific, when, for example, prohibition of skipping a CM section--which is a specific section--has been set in playback control information, if a skip operation is performed by  
20 operating section 118 during CM content playback, playback control information processing section 117 instructs content decoding section 115 to deny this operation.

Operating section 118 accepts content playback  
25 operations from the user. Specifically, operating section 118 accepts operations such as play, stop, pause, rewind, forward, skip, jump,

record, or the like.

In the above configuration, content decoding section 115, license information processing section 116, and playback control information processing section 117 can be made tamper-proof security modules, enabling unauthorized duplication of or tampering with content, license information, and playback control information to be prevented.

License information will now be described using FIG. 2. FIG. 2 is a conceptual drawing showing the relationship between license information, and playback control information and encrypted content.

As shown in FIG. 2, license information 200 is composed of content keys 201 used when content encryption section 101 generates encrypted content 203, and usage conditions 202.

In usage conditions 202, in addition to usage restriction conditions relating to the number of playback times, transfer, duplication, and so forth that can be set with conventional DRM, information has been added indicating that only playback based on playback control information 204 generated by playback control information generation section 103 is permitted.

This makes it possible for playback based on playback control information 204 to be performed by

terminal 110 using usage conditions 202. License information is protected from unauthorized duplication or tampering by means of DRM technology.

Another form of license information will now  
5 be described using FIG. 3. FIG. 3 is a conceptual drawing showing relationships when issuer identification information is attached to license information for encrypted content and playback control information in a content playback control  
10 system of this embodiment.

As shown in FIG. 3, issuer identification information 304 for identifying the issuer of playback control information 303 is attached to playback control information 303, and issuer  
15 identification information 302 is also attached to usage conditions 301.

By using such license information 300 that uses usage conditions 301, playback based only on playback control information 303 to which issuer  
20 identification information 304 that matches issuer identification information 302 attached to usage conditions 301 is attached can be made possible for terminal 110. That is to say, it is possible for only playback based on playback control information  
25 303 to which specified issuer identification information 304 is attached to be permitted for terminal 110.

As a result, terminal 110 (that is, license information processing section 116 of the terminal) can be made to comply with the intended playback of the issuer of playback control information 303. It is also possible to attach a uniquely identifiable identifier to playback control information 303 other than above-described issuer identification information 304, and have license information processing section 116 of terminal 110 perform the same processing.

The form of license information shown in FIG. 4 may also be used. FIG. 4 is a conceptual drawing showing relationships when issuer identification information and an ID (user ID, terminal ID, or the like) are attached to license information and playback control information for encrypted content in a content playback control system of this embodiment.

As shown in FIG. 4, specified issuer identification information 302 and an ID 402 are attached to usage conditions 401 of license information 400. Also, issuer identification information 304 and an ID 404 are attached to playback control information 403.

By this means, issuer identification information 304 and an ID 404 attached to individual issuer identification information 304 can be



attached to usage conditions 401 as information specifying playback control information 403 to be used. Thus, playback based only on playback control information 403 to which issuer identification information 304 and ID 404 that match issuer identification information 302 and ID 402 attached to usage conditions 401 are attached can be made possible for terminal 110.

By using ID 404 in this way, the issuer of playback control information 403 (the person indicated by the issuer identification information) can set a plurality of playback control information 403. That is to say, a plurality of playback control information 403 can be set for the same content.

Playback control information generated by playback control information generation section 103 will now be described in detail.

Playback control information is written in XML (eXtensible Markup Language) or the like. The information set in playback control information is restriction information such as skip prohibition, forward prohibition, prohibition of special playback such as jumping, and so forth, for specific sections divided by means of segmentation metadata.

Playback control information written in XML will now be described. First, the playback control information schema will be described using FIG. 5.

FIG. 5 is a drawing showing an example of the schema of playback control information such as described above.

A playback control information schema enables  
5 segment group information stipulated by the conventional TV-Anytime Forum to be extended to a play control schema 500 that describes playback control, and playback control information to be attached on a segment-by-segment (specific section  
10 by specific section) basis.

As indicated by reference number 501 in the figure, in play control schema 500 the following are set as playback methods: play, stop, pause, forward (fast-forward), rewind, skip (time skip), jump (to  
15 a specified time), record, and copy. In addition, as indicated by reference number 502 in the figure, in play control schema 500 a true (enable)/false (disable) is set for the playback methods indicated by reference number 501.

20 This schema is only one example, and various other settings are also possible, such as restrictions based on playback time, restrictions based on the number of special playback times, and restrictions based on segment playback order.  
25 Special playback refers to a playback method other than normal playback ("play"), that is, a playback method whereby the user does not view a segment in

detail.

As an example, there is a setting whereby, if prohibited special playback is executed by content decoding section 115, it is changed to permitted  
5 special playback.

There are also settings whereby the playback order of a plurality of contents or segments is set, and playback other than in the set playback order is prohibited, or the possible playback time of  
10 specific content or a specific section is set, and playback other than at the set time is prohibited.

A specific description of playback control information will now be described using FIG. 6 and FIG. 7. FIG. 6 and FIG. 7 are drawings showing an  
15 example of metadata describing playback control information in a content playback control system of this embodiment.

Playback control information 60 according to this embodiment is written by means of a  
20 hierarchical structural description using XML. This enables playback control information 60 to have versatility.

Specifically, playback control information 60 describes a plurality of segments 600a through 600c  
25 indicating content sections.

Segments (specific sections) 600a through 600c respectively describe titles 601a through 601c,

descriptions 602a through 602c, segment IDs 603a through 603c which are the segment identification numbers, video IDs 604a through 604c which are identifiers of the video used, segment start times  
5 605a through 605c, and segment lengths 606a through 606c.

Playback control information 60 also describes a playback method having the segment 600a through 600c organization method, restriction of playback  
10 mode, and so forth, as indicated by reference number 607.

Specifically, playback method 607 describes title 608 of playback method 607, description 609 of playback method 607, identification number 610  
15 of playback method 607, used video identifier 615, segment list of used segment 611, and restriction information related to specific segment 612.

Segment list 611 describes the IDs of segments used in playback order. By this means, terminal 110  
20 can be made to perform content playback in the playback order intended by the issuer of playback control information 60.

Restriction information 612 describes ID 613 of the segment subject to control, and restriction  
25 (control) methods 614a through 614c for that segment.

Specifically, <Forward> (fast-forward)

prohibition is described in the area indicated by 614a, <Skip> (time skip) prohibition is described in the area indicated by 614b, and <Jump> (jump to a specified time) prohibition is described in the  
5 area indicated by 614c, that is, prohibition of a playback method whereby this segment is not played back but skipped is described. By this means, time skipping that spans specific sections (segment) of content and jumping to a specified time are  
10 prohibited. To be specific, fast-forwarding and skipping of segment 600b (CM section), and jumping from before segment 600b (CM section) to after segment 600b (CM section), are prohibited.

In this way, a plurality of segments 600a  
15 through 600c, and order and playback restriction information related to these segments 600a through 600c, are described in playback control information 60.

A description method other than the above  
20 described method may be used for playback control information. For example, if the genre code of a segment is CM, playback control information with skipping prohibited or the like set, is created. Then, playback control information processing  
25 section 117 refers to the playback control information, and if the segment information genre code is CM, content decoding section 115 is made to

prohibit skipping. Moreover, operation can be implemented so that skipping is always prohibited when the segment information genre code described in the playback control information is CM, without  
5 explicitly indicating skip prohibition in playback control information.

Playback control information may also be in a form in which control information 612 is described for content that has hierarchical segments.

10 Next, operations in the content playback control system shown in FIG. 1 up to where terminal 110 obtains encrypted content and its license information and playback control information from server 100 will be described with reference to the  
15 processing flow shown in FIG. 8.

First, license information generation section 102 of server 100 extracts from content key storage section 107 content key Kc (hereinafter referred to as "Kc") for encrypting content on which it is wished  
20 to perform playback control. Then license information generation section 102 generates license information containing Kc and Kc usage conditions (step S101 (hereinafter "step S" is referred to simply as "S".)) Here, license  
25 information generation section 102 describes "only playback based on playback control information is permitted for encrypted content" in the usage

conditions.

Next, license information generation section 102 transmits license information generated in S101 to communication section 111 of terminal 110 via communication section 104 (S102). Here, possible methods of communication from server 100 to terminal 110 include transmission via a broadcast network, transmission by means of an IP multicast via an IP network, transmission via an IP network in response to a request from terminal 110, and so forth.

Terminal 110 then receives the license information in communication section 111, and transmits this license information to license information recording section 113. License information recording section 113 records the license information obtained via communication section 111 in a recording medium (S103).

Next, license information generation section 102 of server 100 passes Kc generated in S101 to content encryption section 101 (S104). Content encryption section 101 then obtains content from content storage section 106, and encrypts the obtained content using Kc obtained in S104 (S105).

Next, content encryption section 101 transmits the content encrypted in S105 (encrypted content) to communication section 111 of terminal 110 via communication section 104. Here, possible methods

of communication from server 100 to terminal 110 include transmission via a broadcast network, transmission by means of IP multicast via an IP network, transmission via an IP network in response  
5 to a request from terminal 110, and so forth (S106).

Terminal 110 then receives the encrypted content in communication section 111, and transmits this encrypted content to content recording section 112. Content recording section 112 records the  
10 encrypted content obtained via communication section 111 in a recording medium, still in encrypted form (S107).

Next, playback control information generation section 103 of server 100 generates playback control  
15 information corresponding to the encrypted content encrypted in S105 (S108).

Playback control information generation section 103 then transmits playback control information to communication section 111 of  
20 terminal 110 via communication section 104 (S109). Here, possible methods of communication from server 100 to terminal 110 include transmission via a broadcast network, transmission by means of an IP multicast via an IP network, or transmission via an  
25 IP network in response to a request from terminal 110.

Terminal 110 then receives the playback



control information in communication section 111,  
and transmits this playback control information to  
playback control information recording section 114.  
Playback control information recording section 114  
5 records the playback control information obtained  
via communication section 111 in a recording medium  
(S110).

By means of the above-described processing  
flow, terminal 110 records encrypted content in  
10 content recording section 112, license information  
describing Kc for decoding encrypted content and its  
usage conditions in license information recording  
section 113, and playback control information in  
playback control information recording section 114.

15 In the above-described processing flow,  
terminal 110 obtains license information, encrypted  
content, and playback control information in that  
order, but the order in which these are obtained is  
irrelevant.

20 Also, there are various possible timing  
patterns for the acquisition of license information  
and playback control information by terminal 110,  
such as acquisition at the same time as content  
acquisition, acquisition when content is played  
25 back, periodic collective pre-acquisition, and so  
forth.

Next, operations where terminal 110 decodes

encrypted content in accordance with license information will be described with reference to the processing flow shown in FIG. 9.

When the user requests content playback to  
5 operating section 118, operating section 118 inputs a playback request in response thereto (S201). Then operating section 118 issues a content playback request to content decoding section 115 (S202).

Next, content decoding section 115 issues a  
10 request to license information processing section 116 for license information (Kc and usage conditions) corresponding to the content (S203).

In response, license information processing section 116 obtains license information  
15 corresponding to the content from license information recording section 113 (S204).

License information processing section 116 then returns the license information to content decoding section 115 (S205). "Only playback based  
20 on playback control information is permitted for encrypted content" is described in the usage conditions contained in the license information output by license information processing section 116 here. By describing that only playback based  
25 on playback control information is permitted for encrypted content in license information in the usage conditions, terminal 110 always plays back

encrypted content using playback control information.

Content decoding section 115 then obtains the license information. Next, since "only playback  
5 based on playback control information is permitted for encrypted content" is described in the usage conditions of the obtained license information, content decoding section 115 issues a request for playback control information processing to playback  
10 control information processing section 117 (S206).

In response, playback control information processing section 117 obtains playback control information corresponding to the content from playback control information recording section 114  
15 (S207).

Here, when, for example, issuer identification information 302 and 304 are attached respectively to usage conditions 301 and playback control information 303 as shown in FIG. 3, playback control  
20 information processing section 117 obtains playback control information 303 having issuer identification information 304 which is the same as issuer identification information 302 attached to the usage conditions.

25 By using issuer identification information 302 and 304 indicating the issuer of playback control information in this way, only playback control

information issued by the playback control information issuer is used, and content playback can be controlled as intended by the playback control information issuer.

5       Also, when, for example, issuer identification information 302 and 304, and IDs 402 and 404, are attached respectively to usage conditions 401 and playback control information 403 as shown in FIG. 4, playback control information processing section 10 117 obtains playback control information 403 having issuer identification information 304 and ID 404 which are the same as issuer identification information 302 and ID 402 attached to the usage conditions.

15       By this means, even if a playback control information issuer issues a plurality of playback control information, by using IDs 402 and 404, it is possible to determine which playback control information issued by the issuer should be used.

20       Playback control information processing section 117 then returns completion notification of control preparation for content playback according to playback control information to content decoding section 115 (S208).

25       Next, content decoding section 115 obtains encrypted content corresponding to the playback control information from content recording section

112 (S209). Then content decoding section 115 decrypts and plays back the encrypted content by means of Kc (S210).

By means of the above-described processing  
5 flow, terminal 110 begins content playback based on playback control information.

Next, the processing flow in the content  
playback control system shown in FIG. 1 when a skip  
operation is performed during a CM section while  
10 terminal 110 is performing playback based on the  
playback control information shown in FIG. 6 and FIG.  
7 will be described with reference to the processing  
flow shown in FIG. 10.

When operating section 118 receives a skip  
15 request from the user during CM section playback  
(S301), it passes the skip request to content  
decoding section 115 (S302).

In response, content decoding section 115  
issues a skip possibility/impossibility check  
20 request to playback control information processing  
section 117 (S303).

In response to this request, playback control  
information processing section 117 refers to  
playback control information, recognizes that  
25 skipping is prohibited for the segment being played  
back, and returns an indication that skipping is not  
possible to content decoding section 115 (S304).

To be specific, playback control information processing section 117 refers to restriction information 612 of playback control information 60 shown in FIG. 7. Then playback control information processing section 117 refers to ID 613 of restriction information 612 and recognizes a segment subject to restrictions. In this case, since ID 603b of CM related segment 600b is described in ID 613, playback control information processing section 117 recognizes that CM related segment 600b is subject to playback restrictions.

Next, playback control information processing section 117 refers to restriction (control) methods 614a through 614c, and more specifically, recognizes what kind of restrictions have been set for CM related segment 600b. In this case, "forward," "skip," and "jump," are specified as not possible in restriction methods 614a through 614c, and therefore playback control information processing section 117 recognizes that CM related segment 600b is a segment for which skipping is not possible. Playback control information processing section 117 then returns an indication that skipping is not possible to content decoding section 115.

In response to this, having obtained an indication that skipping is not possible in S304, content decoding section 115 does not comply with

the skip request in S302, but continues content playback using the playback method currently being employed (S305).

If, at this time, a playback method already  
5 prohibited in the playback control information, such as skip or forward, is in progress, content decoding section 115 performs processing to return to a playback method permitted in the playback control information. Also, if jump processing or  
10 skip processing that skips a segment subject to control in the playback control information has been performed, content decoding section 115 discontinues this processing.

When content decoding section 115 receives an  
15 indication that skipping is not possible in S304, it may transmit a "skipping not possible" indication to output terminal 130 and notify the user that the operation is prohibited.

Also, when content decoding section 115  
20 receives skip requests, it is possible for content decoding section 115 not to inquire about a skip possibility/impossibility to playback control information processing section 117 each time there is an operation request, but to obtain playback  
25 control information from the playback control information processing section when there is a playback request and make a decision in content

decoding section 115.

By performing content playback using playback control information as described above, it is possible for terminal 110 not to accept a playback method prohibited in the restriction method described in the playback control information. That is to say, terminal 110 can be made to comply with playback intended by the playback control information issuer (broadcaster).

10 In this processing flow, only skipping has been taken as an example, but the same kind of processing also applies to the other operations (forward and jump) described in playback control information 60 in FIG. 6 and FIG. 7. By means of this processing flow, a terminal can be made to comply with playback based on playback control information.

As described above, according to Embodiment 1 content playback is performed based on playback control information that describes a restriction method related to the playback method (mode) of a specific section of content, and it is therefore possible to perform control related to the playback method of a specific section of content.

Furthermore, according to Embodiment 1, since a playback restriction method is described not in content itself but in playback control information, a plurality of contents need not be held for each



playback control method. Also, since it is only necessary to store a comparatively small amount of playback control information for each playback control method, the storage section of terminal 110  
5 can be made compact.

Moreover, according to Embodiment 1, since a mode is used whereby playback control information and license information are transmitted separately from server 100 to terminal 110, it is possible to  
10 prevent communication from becoming heavy due to simultaneous transmission of playback control information and license information. Also, when the communication network is heavy, playback control information may be transmitted beforehand  
15 without using communication, and only license information may be transmitted by communication. Furthermore, if a mode is adopted whereby only license information is stored in a tamper-proof security module of terminal 110, terminal  
20 implementation costs can be reduced.

Also, the validity of playback control information may be checked in terminal 110 by means of a method such as attaching an electronic signature to playback control information. By this  
25 means, it is possible to prevent content playback that runs counter to the intentions of the playback control information issuer due to tampering with the

playback control information.

During playback of a section for which a predetermined operation is prohibited by playback control information, the GUI of operating section 118 may be changed as appropriate to indicate to the user that the operation is prohibited. For example, the color of the forward button on the remote controller may be changed during a section for which forwarding is prohibited, or displayed as different from the color of other non-prohibited operations, or it may be made impossible to press the forward button so that an operation prohibited by the playback control information processing section cannot be accepted by operating section 118. Another possibility is to impose a character or symbol indicating that fast-forwarding cannot be performed on the playback screen. In this case, information of an operation prohibited for the playback section is passed from playback control information processing section 117 to operating section 118, and operating section 118 changes appropriately to reflect that information.

By this means the user can easily recognize currently permitted operations and prohibited operations.

Also, preview license information and actual-viewing license information may be prepared

separately for the same content, and that playback is possible for only a content preview may be described in playback control information corresponding to preview license information. By  
5 this means, a regular license purchaser may be issued an actual-viewing license and enabled to actually view content, while someone who has not purchased a regular license is issued preview license information and allowed to view only a  
10 content preview.

A mode may also be used whereby operations of server 100 or terminal 110 according to Embodiment 1 are stored in a recording medium as a program, and this program is executed by a general-purpose  
15 computer.

(Embodiment 2)

A content playback control system according to Embodiment 2 of the present invention performs  
20 playback possibility/impossibility control based on a time period.

FIG. 11 is a block diagram showing the configuration of a content playback control system according to Embodiment 2 of the present invention.  
25 Parts identical to parts already described in Embodiment 1 are assigned the same codes, and detailed descriptions thereof are omitted.

Terminal 1110 of a content playback control system according to Embodiment 2 is provided with current time management section 1112. Current time management section 1112 is a clock or the like that manages the current time. Server 1100 is also provided with current time management section 1101. Current time management section 1101 and current time management section 1112 have the same configuration.

Playback control information generation section 1102 of server 1100 generates playback control information describing a content playback restriction (control) method according to time information. Playback control information generation section 1102 transmits generated playback control information to terminal 1110 via communication section 104 and channel 120.

A playback control information processing section 1111 of terminal 1110 controls playback of content in content decoding section 115 based on playback control information generated by playback control information generation section 1102.

The schema of playback control information generated by playback control information generation section 1102 will now be described using FIG. 12. FIG. 12 is a drawing showing an example of the schema of playback control information

according to Embodiment 2.

Playback control information schema 1200 according to Embodiment 2, makes a definition for content playback restriction information based on  
5 time as indicated by reference number 1201 in the figure. Also, schema 1200 makes a definition so as to specify content playback restriction information based on time, as indicated by reference number 1202 in the figure. Specifically, schema 1200 makes a  
10 definition for start time 1203 and end time 1204 subject to restrictions, and restriction method 1208 indicating how content playback is restricted at the restricted time.

Schema 1200 also makes a definition so as to  
15 specify where time information is to be obtained, as indicated by reference number 1205 in the figure. Specifically, schema 1200 makes a definition so as to specify whether time information is to be obtained from current time management section 1112  
20 of terminal 1110, as indicated by reference number 1206 in the figure, or is to be obtained from current time management section 1101 of server 1100, as indicated by reference number 1207 in the figure.

A specific description of playback control  
25 information according to Embodiment 2 will now be described using FIG. 13. FIG. 13 is a drawing showing an example of metadata describing playback

control information in a content playback control system of Embodiment 2.

Specifically, playback control information 1300 according to Embodiment 2 describes  
5 restriction information for one segment. To be specific, playback control information 1300 describes segment ID 1301, ID 1302 of video used in the segment, segment title 1303, segment description 1304, and segment section information  
10 1305.

Playback control information 1300 also describes restriction information for the segment in the area indicated by reference number 1306 in the figure. Specifically, restriction information  
15 1306 describes start time 1307 and end time 1308 subject to restrictions, and restriction method (in this example, playback impossibility) 1309 for the restricted time.

Restriction information 1306 also describes  
20 acquisition location information 1310 indicating where the current time is to be obtained. In this case, acquisition location information 1310 describes that the current time is to be obtained from current time management section 1101 of server  
25 1100.

By obtaining the current time from server 1100 in this way, current time management can be

performed accurately. Also, in terminal 1110, content playback can be controlled accurately even if time information managed by current time management section 1112 is tampered with.

5        Only information for one segment is described in playback control information 1300 shown in FIG. 13, but information for a plurality of segments may be described, and different restriction information may be described for each segment.

10       Next, content playback processing in a content playback control system according to Embodiment 2 will be described with reference to the processing flow shown in FIG. 14.

      When the user inputs a content playback request  
15    from operating section 118, operating section 118 transmits a content playback request to content decoding section 115 (S1400).

      In response to this, content decoding section 115 transmits playback control information  
20    processing section 1111 a request for information related to playback possibility/impossibility as to whether or not content may be played back (S1401).

      In response to this, playback control information processing section 1111 refers to  
25    playback control information recording section 114 and obtains playback control information.

      Next, playback control information processing

section 1111 refers to the playback control information and determines where the current time is to be obtained. In the case of the playback control information shown in FIG. 13, for example, 5 the description indicates that the current time is to be obtained from current time management section 1101 of server 1100, as indicated by reference number 1301 in the figure, and therefore playback control information processing section 1111 10 transmits a time information acquisition request to server 1100 via communication section 111.

In response to this, server 1100 obtains a current time acquisition request via communication section 104, and transmits this to current time 15 management section 1101. Current time management section 1101 then obtains the current time acquisition request and transmits the current time to terminal 1110 via communication section 104.

Communication section 111 of terminal 1110 20 then obtains the transmitted current time and transmits it to playback control information processing section 1111, and playback control information processing section 1111 obtains the current time (S1402).

25 If the playback control information describes an indication that the current time is to be obtained from current time management section 1112 of



terminal 1110, playback control information processing section 1111 obtains the current time from current time management section 1112 (S1402).

Next, playback control information processing  
5 section 1111 refers to the playback control information, and obtains restricted time related information. In the example in FIG. 13, playback control information processing section 1111 obtains start time 1307 and end time 1308. Playback control  
10 information processing section 1111 also refers to the playback control information and obtains restriction method related information. In the example in FIG. 13, playback control information processing section 1111 obtains restriction method  
15 1309 describing an indication that playback is not possible.

Playback control information processing section 1111 then compares the current time obtained in S1402 with restricted time related information  
20 described in the playback control information, and if these times match, transmits the restriction method described in the playback control information--in this case, an indication that content cannot be played back--to content decoding  
25 section 115 (S1403).

In response to this, content decoding section 115 performs playback impossible processing, that

is, processing whereby decoding of encrypted content is not performed, and terminates processing (S1404).

As described above, according to Embodiment 2,  
5 content playback control can be performed using time information. By this means, for example, by suppressing playback of stored content at prime time, it is possible to ensure that content being broadcast is viewed.

10 Also, according to Embodiment 2, control can be performed so that the current time is inquired to server 1100. By this means, it is possible to prevent unauthorized use of content by tampering with the current time in terminal 1110.

15 It is also possible to combine Embodiment 1 and Embodiment 2, and perform control so that specific playback is impossible at a predetermined time.

Also, if a content playback request is received from operating section 118 during a  
20 playback-prohibited time period described in playback control information, that operation may be made unacceptable. To indicate that content playback cannot be performed during a playback-prohibited time period, the color of the  
25 play button or the like of operating section 118 may be changed, or an indication that content playback is not possible may be displayed.

Furthermore, if a prohibited time period is entered during content playback, content playback may be made to stop automatically.

Although playback restriction based on time  
5 has been described, playback disabling or enabling restrictions may also be implemented based on day-of-the-week or date restrictions.

(Embodiment 3)

10 A content playback control system according to Embodiment 3 of the present invention performs playback possibility/impossibility control based on a viewing environment.

FIG. 15 is a block diagram showing the  
15 configuration of a content playback control system according to Embodiment 3 of the present invention. Parts identical to parts already described are assigned the same codes, and detailed descriptions thereof are omitted.

20 Terminal 1510 of a content playback control system according to Embodiment 3 is provided with illuminance detection section 1512. Illuminance detection section 1512 detects the illuminance (lux) of the environment in which terminal 1510 is  
25 located.

Playback control information generation section 1502 of server 1500 generates playback

control information describing content playback  
restriction (control) information according to  
illuminance information. Playback control  
information generation section 1502 transmits  
5 generated playback control information to terminal  
1510 via communication section 104 and channel 120.

Playback control information processing  
section 1511 of terminal 1510 controls playback of  
content in content decoding section 115 based on  
10 playback control information generated by playback  
control information generation section 1502.

Next, the schema of playback control  
information generated by playback control  
information generation section 1502 will now be  
15 described using FIG. 16. FIG. 16 is a drawing  
showing an example of the schema of playback control  
information according to Embodiment 3.

Playback control information schema 1600  
according to Embodiment 3, makes a definition for  
20 content playback restriction information based on  
illuminance as indicated by reference number 1601  
in the figure. Also, schema 1600 makes a definition  
so as to specify a restriction method based on  
illuminance, as indicated by reference number 1602  
25 in the figure. Specifically, schema 1600 makes a  
definition for minimum illuminance 1604 and maximum  
illuminance 1605 indicating illuminance subject to

restrictions, and restriction method 1603 indicating how content is to be played back at minimum illuminance 1604 or higher and at maximum illuminance 1605 or lower.

5       Next, a specific description of playback control information according to Embodiment 3 will now be described using FIG. 17. FIG. 17 is a drawing showing an example of metadata describing playback control information in a content playback control  
10       system of Embodiment 3. Parts identical to parts already described are assigned the same codes, and detailed descriptions thereof are omitted.

Playback control information 1700 according to Embodiment 3 describes restriction information for  
15       the segment in the area indicated by reference number 1701 in the figure. Specifically, restriction information 1701 describes minimum illuminance 1702 subject to restrictions, and restriction method (in this example, playback  
20       possibility) 1703 in the case of minimum illuminance 1702 or higher.

Only information relating to one segment is described in playback control information 1700 shown in FIG. 17, but information for a plurality  
25       of segments may be described, and different restriction information may be described for each segment.

Next, content playback processing in a content playback control system according to Embodiment 3 will be described with reference to the processing flow shown in FIG. 18.

5        When the user inputs a content playback request from operating section 118 (S1801), operating section 118 transmits a content playback request to content decoding section 115 (S1802).

10        In response to this, content decoding section 115 transmits a request for information related to playback possibility/impossibility as to whether or not content may be played back to playback control information processing section 1511 (S1803).

15        In response to this, playback control information processing section 1511 refers to playback control information recording section 114 and obtains playback control information.

20        Next, playback control information processing section 1511 issues a request to illuminance detection section 1512 for illuminance information concerning the environment in which terminal 1510 is located (S1804). In response to this request, illuminance detection section 1512 transmits illuminance information concerning the environment  
25        in which terminal 1510 is located to playback control information processing section 1511 (S1805).

Playback control information processing section 1511 then refers to the playback control information and obtains information relating to illuminance subject to restrictions. In the  
5 example in FIG. 17, playback control information processing section 1511 obtains minimum illuminance 1702. Playback control information processing section 1511 refers to the playback control information and obtains restriction method related  
10 information. In the example in FIG. 17, playback control information processing section 1511 obtains restriction method 1703 describing an indication that playback is possible.

Playback control information processing  
15 section 1511 then determines whether the illuminance information obtained in S1805 corresponds to the illuminance subject to restrictions described in the playback control information, and if it does, transmits the  
20 restriction method described in the playback control information--in this case, an indication that content playback is possible--to content decoding section 115 (S1806).

In response to this, content decoding section  
25 115 performs playback processing, that is, processing whereby encrypted content is decoded and output to output terminal 130, and terminates

processing (S1807).

As described above, according to Embodiment 3 content playback control can be performed using illuminance information of the environment in which terminal 1510 is located. By this means, it is possible, for example, to prevent an animation program containing scenes with sharp luminance variations from being viewed in a dark room.

Also, if a content playback request is received from operating section 118 under conditions corresponding to the playback control illuminance described in the playback control information, that operation may be made unacceptable. To indicate that content playback cannot be performed when terminal 1510 is in the illuminance subject to playback control, the color of the play button or the like of operating section 118 may be changed, or an indication that content playback is not possible may be displayed. If a playback request is made again after an indication that content playback is not possible has been displayed, the processing of S1801 through S1807 may be repeated.

Furthermore, if the environment of terminal 1510 enters the illuminance subject to playback control during content playback, playback may be made to stop automatically.

Playback control information for controlling



content playback may be generated using environment information other than illuminance information, and content playback control may be performed using environment information other than illuminance  
5 information.

(Embodiment 4)

A content playback control system according to Embodiment 4 of the present invention performs  
10 playback possibility/impossibility control based on a user attribute.

FIG. 19 is a block diagram showing the configuration of a content playback control system according to Embodiment 4 of the present invention.  
15 Parts identical to parts already described are assigned the same codes, and detailed descriptions thereof are omitted.

Terminal 1910 of a content playback control system according to Embodiment 4 is provided with  
20 attribute management section 1912. Attribute management section 1912 manages information related to the user of terminal 1910, that is, a user attribute. A mode of attribute management section 1912 may be used whereby the user inputs a user  
25 attribute from an IC card or the like, or a mode may be used whereby the user inputs a user attribute from operating section 118.

User attribute information includes a user's age, a user's terminal performance, the surrounding environment of a user's terminal, a user's area information (address), and so forth. A mode may be  
5 used whereby user information managed by a provider is set in attribute management section 1912 via channel 120.

Playback control information generation section 1902 of server 1900 generates playback  
10 control information describing playback control by means of user attribute information. Playback control information generation section 1902 transmits generated playback control information to terminal 1910 via communication section 104 and  
15 channel 120.

Playback control information processing section 1911 of terminal 1910 controls playback of content in content decoding section 115 based on playback control information generated by playback  
20 control information generation section 1902.

The schema of playback control information generated by playback control information generation section 1902 will now be described using FIG. 20. FIG. 20 is a drawing showing an example  
25 of the schema of playback control information according to Embodiment 4.

Playback control information schema 2000

according to Embodiment 4 makes a definition for content playback restriction information based on a user attribute as indicated by reference number 2001 in the figure. Also, schema 2000 makes a definition so as to specify restriction information based on a user attribute, as indicated by reference number 2002 in the figure. Specifically, schema 2000 makes a definition for minimum age 2004 and maximum age 2005 subject to restrictions, and restriction method 2003 indicating how content is to be played back in the case of minimum age 2004 or higher and in the case of maximum age 2005 or lower.

A specific description of playback control information according to Embodiment 4 will now be described using FIG. 21. FIG. 21 is a drawing showing an example of metadata describing playback control information in a content playback control system of Embodiment 4. Parts identical to parts already described are assigned the same codes, and detailed descriptions thereof are omitted.

Playback control information 2100 according to Embodiment 4 describes restriction information for the segment in the area indicated by reference number 2101 in the figure. Specifically, restriction information 2101 describes minimum age 2102 subject to restrictions, and restriction

method (in this example, playback possible) 2103 in the case of minimum age 2102 or higher.

Only information for one segment is described in playback control information 2100 shown in FIG. 21, but information for a plurality of segments may be described, and different restriction information may be described for each segment.

Next, content playback processing in a content playback control system according to Embodiment 4 will be described with reference to the processing flow shown in FIG. 22.

When the user inputs a content playback request from operating section 118 (S2201), operating section 118 transmits a content playback request to content decoding section 115 (S2202).

In response to this, content decoding section 115 transmits a request for information related to playback possibility/impossibility as to whether or not content may be played back to playback control information processing section 1911 (S2203).

In response to this, playback control information processing section 1911 refers to playback control information recording section 114 and obtains playback control information.

Next, playback control information processing section 1911 issues a request to attribute management section 1912 for a user attribute of

terminal 1910--in this case, age information (S2204). In response to this request, attribute management section 1912 transmits user age information of terminal 1910 to playback control  
5 information processing section 1911 (S2205).

Playback control information processing section 1911 then refers to the playback control information and obtains information related to an age subject to control. In the example in FIG. 21,  
10 playback control information processing section 1911 obtains minimum age 2102. Playback control information processing section 1911 refers to the playback control information and obtains restriction method related information. In the  
15 example in FIG. 21, playback control information processing section 1911 obtains restriction method 2103 describing an indication that playback is possible.

Playback control information processing  
20 section 1911 then determines whether the age information obtained in S2205 corresponds to the age subject to restrictions described in the playback control information, and if it does, transmits the restriction method described in the playback  
25 control information --in this case, an indication that content playback is possible-- to content decoding section 115 (S2206).

In response to this, content decoding section 115 performs playback processing, that is, processing whereby encrypted content is decoded and output to output terminal 130, and terminates  
5 processing (S2207).

As described above, according to Embodiment 4 content playback control can be performed using a user attribute --in this case, user's age-- of terminal 1910. By this means, for example, if  
10 content includes a section containing adult-oriented video, viewing of that section can be restricted to those aged 20 or over.

Also, if a content playback request is received from operating section 118 from a user of an age  
15 subject to restrictions described in the playback control information, that operation may be made unacceptable. To indicate that content playback cannot be performed when the user of terminal 1910 is of an age subject to restrictions, the color of  
20 the play button or the like of operating section 118 may be changed, or an indication that content playback is not possible may be displayed.

Schema 2000 shown in FIG. 20 may also be defined so as to specify where a user attribute is to be  
25 obtained. Specifically, schema 2000 may be defined so as to specify whether a user attribute is to be obtained from terminal 1910 or from server 1900.

Age has been used as a user attribute in the above description, but another attribute may also be used.

In Embodiment 4, content playback control  
5 based on a user attribute has been described, but content playback control may also be performed based on a terminal attribute.

In the case of this mode, attribute management section 1912 manages attribute of terminal 1910, for  
10 example, area information indicating where terminal 1910 is located.

Also, playback control information generation section 1902 of server 1900 generates playback control information describing playback control  
15 based on terminal attribute information.

A schema of playback control information generated by playback control information generation section 1902 in the case of this mode will be described using FIG. 23. FIG. 23 is a drawing  
20 showing another example of the schema of playback control information according to Embodiment 4.

Playback control information schema 2300 defines content playback restriction information based on a terminal attribute as indicated by  
25 reference number 2301 in the figure. Also, schema 2300 makes a definition so as to specify restriction information based on a terminal attribute, as

indicated by reference number 2302 in the figure. Specifically, schema 2300 makes a definition for terminal attribute 2303 subject to restrictions, and restriction method 2304 indicating how content  
5 is to be played back in the case of terminal attribute 2303.

A specific description of playback control information according to this mode will now be described using FIG. 24. FIG. 24 is a drawing  
10 showing another example of metadata describing playback control information in a content playback control system of Embodiment 4. Parts identical to parts already described are assigned the same codes, and detailed descriptions thereof are omitted.

15 Playback control information 2400 describes playback restriction information for the segment in the area indicated by reference number 2401 in the figure. Specifically, restriction information 2401 describes a terminal attribute subject to  
20 restrictions--in this case, area information 2402--and restriction method (in this example, playback impossibility) 2403 in the case of area information 2402.

Only information for one segment is described  
25 in playback control information 2400 shown in FIG. 24, but information for a plurality of segments may be described, and different restriction information



may be described for each segment.

In content playback processing in a content playback control system in this mode, playback control information processing section 1911 first  
5 issues a request to attribute management section 1912 for an attribute of terminal 1910, --in this case, a request for area information indicating where terminal 1910 is located. In response to this, attribute management section 1912 transmits area  
10 information of terminal 1910 to playback control information processing section 1911.

Playback control information processing section 1911 then refers to the playback control information and obtains information related to an  
15 area subject to control. In the example in FIG. 24, playback control information processing section 1911 obtains area information 2402. Playback control information processing section 1911 refers to the playback control information and obtains  
20 restriction method related information. In the example in FIG. 24, playback control information processing section 1911 obtains restriction method 2403 describing an indication that playback is impossible.

25 Playback control information processing section 1911 then determines whether the obtained area information corresponds to the area subject to

restrictions described in the playback control information, and if it does, transmits the restriction method described in the playback control information--in this case, an indication  
5 that content playback is not possible--to content decoding section 115.

In response to this, content decoding section 115 performs playback-impossible processing, that is, processing whereby decoding of encrypted  
10 content is not performed, and terminates processing.

In this way, content playback control can be performed using a terminal attribute --in this case, area information-- of terminal 1910. By this means,  
15 when a sports event is being broadcast, for example, more people can be induced to actually attend the event by prohibiting playback in the area around the location where the event is being held.

Content playback control may also be performed  
20 by combining Embodiment 2 through Embodiment 4, and combining time, terminal environment (illuminance), terminal user age, and terminal location. Moreover, Embodiment 1 may be combined with this and restrict special playback under the above conditions.

25 The present application is based on Japanese Patent Application No. 2003-366604 filed on October 27, 2003, and Japanese Patent Application No.

2004-308807 filed on October 22, 2004, the entire content of which is expressly incorporated herein by reference.

5 Industrial Applicability

The present invention enables a terminal to be made to comply with playback based on playback control information by distributing playback control information together with content via a  
10 broadcast network, IP network, or suchlike channel, and thus enables a user to be made to comply with a content playback mode intended by a broadcaster (playback control information creator). The present invention is widely applicable not only to  
15 fixed terminals such as computers, televisions, and hard disk recorders, but also to portable terminals, in-vehicle terminals, and so forth.